


FL-CC2514-2M

Dimensions



Unit: mm




Scale 100 : 100

FL-CC2514-2M Product specifications

Format size	2/3, 1/1.8, 1/2, 1/3" format	
Focal length	25 mm	
Maximum aperture ratio	1:1.4	
Iris range	1.4~16	
Mount	C	
Horizontal angle of view	1/4" format	8.2°
	1/3" format	11.0°
	1/2" format	14.6°
	2/3" format	20.0°
Minimum object distance	0.25 m	
Back focal length	11.50 mm	
Filter size	27 P=0.5 mm	
Dimensions	φ29.5×32 mm	
Weight	55 g	
Remarks	Focus & Iris lock screws	

FL-CC3516-2M

Dimensions



Unit: mm




Scale 100 : 100

FL-CC3516-2M Product specifications

Format size	2/3, 1/1.8, 1/2, 1/3" format	
Focal length	35 mm	
Maximum aperture ratio	1:1.6	
Iris range	1.6~16	
Mount	C	
Horizontal angle of view	1/4" format	6.1°
	1/3" format	8.1°
	1/2" format	10.8°
	2/3" format	14.8°
Minimum object distance	0.4 m	
Back focal length	11.85 mm	
Filter size	27 P=0.5 mm	
Dimensions	φ29.5×35.4 mm	
Weight	64 g	
Remarks	Focus & Iris lock screws	

FL-CC5028-2M

Dimensions



Unit: mm




Scale 100 : 100

FL-CC5028-2M Product specifications

Format size	2/3, 1/1.8, 1/2, 1/3" format	
Focal length	50 mm	
Maximum aperture ratio	1:2.8	
Iris range	2.8~22	
Mount	C	
Horizontal angle of view	1/4" format	4.1°
	1/3" format	5.5°
	1/2" format	7.3°
	2/3" format	10.0°
Minimum object distance	0.9 m	
Back focal length	21.03 mm	
Filter size	27 P=0.5 mm	
Dimensions	φ29.5×34 mm	
Weight	55 g	
Remarks	Focus & Iris lock screws	

FL-CC7528-2M

Dimensions



Unit: mm



Scale 65 : 100

FL-CC7528-2M Product specifications

Format size	2/3, 1/1.8, 1/2, 1/3" format	
Focal length	75 mm	
Maximum aperture ratio	1:2.8	
Iris range	2.8~32	
Mount	C	
Horizontal angle of view	1/4" format	2.8°
	1/3" format	3.8°
	1/2" format	5.0°
	2/3" format	6.9°
Minimum object distance	0.7 m	
Back focal length	30.94 mm	
Filter size	30.5 P=0.5 mm	
Dimensions	φ34×59.6 mm	
Weight	125 g	
Remarks	Focus & Iris lock screws	